CITY OF JUNEAU STREET OPENING PERMIT

				Date:			
Doing work	k for:		_				
Subcontractor:			#313 \$25.00 Fee Paid YES NO				
	eposit will be sent to subcontractor		_	Receipt 1	Number		
Address:			_				
				#312	\$600.00 Deposit Paid	YES	NO
Phone:			_	Receipt N	umber		
Anticipated V	Work Dates: From		To:				
Street Name:		Location-From :		To:			
Purpose:	☐ Retire Service						
	☐ Leak Repair	☐ Other:			<u>-</u>		
Location	\square Roadway	☐ Terrace	\Box O	ther:			
Street Surface	e: Concrete	☐ Blacktop ☐ G	ravel	☐ Other:			
Type of Patcl	h: Backfill		Surf	face			
Required Dat	te of Completion:						
Proof of Insu	rance – (Contractors Req	uired to have \$1,000,00	0.00 Mi	inimum):	☐ Yes ☐ No		
Provide City	with Deposit of \$600.00	Check – to be returned	upon sat	tisfactory cor	npletion of project.		
to other utilit	varranty is mandatory fies or property caused by the termit and agree to the termitand agree to the terminand agre	you or your contractor.	. By sig				
the City of Ju	ıneau Common Council a				accordance with the rule	s set for	th by
•							
(For Office Use O							
Deposit Retu	rned: YES NO	Approved By	y:				
Comments:_							
	Customer – Street Dep						

Contact Number:

Joe Ludtke, Street Superintendent: 920-210-7501

Alex Smudde, Wastewater Superintendent: 920-386-4815

Nick Gahlman, Electric Superintendent: 920-210-3445

Dave Beal, Chief of Police 920-210-8592

City Hall 920-386-4800

Diggers Hot Line: 1-800-242-8511

Permit Holder Must:

• Call Diggers hotline

- Provide barricade for the site
- Back fill must be compacted
- Site to be restored to the original condition or better
- Contact the City Garage (Joe Ludtke) when the job is done

12.08.040 Street excavations.

- A. Permit Required. No person shall excavate or cause excavation to be made in any street right-of-way, alley or other public ground, without first having secured a permit for same from the director of public works.
- B. Protection of the Public. No permit shall be issued unless the method of construction and location of the work to be performed shall be such that the public safety and convenience will not be impaired. The permittee shall erect such barriers, warning lights and signs as to adequately inform the traveling public of the nature and location of the work being performed.
- C. Repair of Street Excavations.
 - 1. The party to whom a permit is issued, under this section shall complete the permitted work involved within the time specified in the permit granted, except a reasonable time extension may be granted due to conditions which may prevent the permittee from completing such work within the time specified in the original permit.
 - 2. Excavated Materials. When any excavation is made in any street right-of-way or other public grounds, all unsuitable material, as determined by the director of public works, shall be removed from the site. The excavation shall be backfilled with suitable granular material, as specified by the director of public works, or other official, and such fill shall be properly placed by mechanical tamping in not more than twelve (12) inch layers.
 - 3. Gravel Surfaced Streets. Backfilling shall be done as in subsection C2 above to the existing surface elevation.
 - 4. Concrete Surfaced Streets. When concrete surface is to be removed, the concrete shall be saw-cut at least one foot outside of the perimeter of the excavation and the concrete shall be removed to the sub-base of the street. The excavation shall be backfilled as required in subsection C2 above. Concrete surfacing shall be replaced in accordance with city specifications.
 - 5. Bituminous Paved Streets. When bituminous street surfacing is removed, the pavement or surfacing shall be saw-cut at least one foot outside the perimeter of the excavation and removed to the sub-base of the street. The excavation shall be backfilled as required in subsection C2 above. The bituminous surfacing shall be replaced according to city specifications.
 - 6. Terrace (Tree Border). Excavations in the terrace shall conform to subsection C2 above, except the top four-inch layer of backfill shall be of a good grade of top soil, free of lumps or clods, seeded with grass and smoothly raked to a finish. (Prior code § 4-2-4)

Revised 6/2016